

# TracingPro™

## LINE MARKER ACRYLIC PAINT AEROSOL



### AEROSOL LINE MARKING PAINT:

The Tracing Pro aerosol line marking paint was designed to secure workplace safety through safety signage compliance for yourself, your employees, your visitors and your clients. With just one product, it allows you to make your markings outdoors as well as indoors, with high quality and exceptional resistance to clogging. It guarantees a precise spray and a high flow rate over a longer distance than its competitors and allows you to carry out your markings more quickly and at a lower cost.

### PRODUCT FEATURES:

- Operated with the PureSpray application trolley
- Resistance to clogging
- 90m coverage within 75 mm line width with 1 can

### CUSTOMER BENEFITS:

- Touch-dry in 11 minutes, light traffic-ready in 60 minutes and heavy traffic-ready within 24 hours.
- Brightness, contrast, and durability, it is an industrial-grade marking paint
- Withstands the most severe conditions (UV, solvents, pedestrian, car or forklift-truck traffic) indoors or outdoors.

### COLOURS AVAILABLE:



### RECOMMENDED USE:



Car Parks



Warehouse



Facilities

### APPLICATION METHOD:



Sprayed

**SURFACE PREPARATION:**

All surfaces must be free of any dust, damp or contamination.

Concrete - before applying **Spectrum Tracing Pro** on new concrete, wait for 3 to 4 weeks to allow the concrete to dry (DTU standard) and the acid evaporation. Greater amounts of aerosol will be required for line marking on coarser concrete.

Asphalt - it is advisable to wait at least 28 days before marking on a new asphalt coating to avoid damage to the paint. Depending on the climate conditions after laying the asphalt, this period may have to be extended by one or two weeks.

Painted Surfaces - **Spectrum Tracing Pro** is suitable for most floor coatings, however a compatibility test is always recommended prior to applying markings.

**MIXING:**

Shake the can vigorously upside down to mix the paint thoroughly (the balls should be heard clearly).

**APPLICATION:**

Manually or with our application equipment (**PureSpray** Application Trolley). Use upside down and adjust height of application in accordance with your required line width.

The surface to be painted must be well prepared for an excellent adherence of the paint. Clean surface to be free of dust, dirt and grease. At the time of application, surface must be dry and temperature not less than 5°C for optimal performance.

For a good quality line, the first application must be a thin coat. The second and possibly third must be carried out more slowly so that a good deposit of paint is achieved.

**AFTER USE:**

Purge can in upright position (until only gas is released), to clean the valve and diffuser.

**DO NOT** apply when the air or surface temperature is below 5°C or less than 3°C above dew point, or if this is likely to occur during the curing period.

**DO NOT** apply when there is rain, mist, fog, or snow imminent; when humidity is high or the surface is wet with condensation or likely to be during the drying period.

**CURING:**

Touch Dry: 11 mins @ 15°C.  
Light Traffic: 60 mins @ 15°C  
Heavy Traffic: 24 hours @ 15°C

**TECHNICAL:**

**COVERAGE:**  
90 m coverage within 75 mm line width with 1 aerosol can, on smooth surface (concrete) at optimal speed.

**AFTERCARE AND MAINTENANCE:**

To ensure the best cleanable finish, lines can be covered by **Spectrum ClearSeal W260** varnish to increase time lasting and resistance to dirt. Use water and mild detergent to wash line.

**STORAGE AND PACKAGING:**

The aerosols must be kept from 5°C to 25°C and from 50 to 60% relative humidity.

**Do not** expose to temperatures above 50°C. To be kept out of any source of ignition, heat or direct sunlight.

**SHELF LIFE:**

12 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

**SIZES AVAILABLE:**

Available in 750ml aerosols - 6 cans / box.

**HEALTH AND SAFETY:**

Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on 023 9220 0606.